

Palmare KTE5

Rugged Android PDA



Octa Core
2.0GHz



6GB RAM
128GB ROM



OS Android 13



5.5 inch
720X1440



Certification
IP65

VIEWS



Palmare KTE5

Rugged Android PDA

FEATURES

BASIC PARAMETERS		PERFORMANCE PARAMETER	
Dimension	160 x 76 x 15.5mm	CPU	Qualcomm Snapdragon™ 662 Octa-core, 2.0 GHz
Weight	Device unit 287g	OS	Android 13 GMS
Device Color	Black	RAM	6GB
LCD	5.5 inch FHD, 18:9, IPS IGZO 1440 x 720	ROM	128GB
Touch Panel	Multi-touch panel, gloves and wet hands supported	Battery Capacity	4300mAh
Camera	Rear 13MP Autofocus with flash		
I/O	2 microphones, 1 for noise cancellation; 1 speaker; receiver 1 slot for Nano SIM card, 1 slot for Nano SIM or TF card (max 128GB), USB Type-C, USB 3.1, OTG, extended thimble;	Battery Type	Removable Battery
		Endurance	Standby: over 300 hours Continuous use: over 12 hours (depending on user environment) Charging time: 2.5 hours (charge device by standard adaptor and USB cable)
Power	AC100V ~ 240V, 50Hz/60Hz, Output DC 5V/2A		
Sensor	Accelerometer sensor, light sensor, proximity sensor, gravity sensor, Sound, LED indicator, vibrator, fingerprint sensor		



Warehouse



Logistic



Ho.Re.Ca.



KRELL Informatica S.r.l. – Via Appia Nuova Km 19,200 – 00047 Marino (RM)

Tel 06 93 00 547 - 06 93 52 489 E-mail: info@krell.it – Sito: www.krell.it

Palmare KTE5

Rugged Android PDA

FEATURES

COMMUNICATION		BARCODE SCANNER	
WIFI	Support 802.11 a/b/g/n/ac/ax ready/d/e/h/i/k/r/v, 2.4G/5G dual-band, IPV4, IPV6, 5G PA;	2D SYMBOLOGIES	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
WWAN (Asia, Eurpe)	2G: 850/900/1800/1900 MHz 3G: CDMA EVDO: BCO WCDMA: 50/900/1900/2100MHz TD-SCDMA: A/F(B34/B39) 4G: B1/B3/B5/B7/B8/B20/B38/B39 B40/B41	1D SYMBOLOGIES	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX),etc.
NFC	13.56 MHz, ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.	RELIABILITY	
		Store Temperature	-40 °C ~ 70 °C
		Operate Temperature	-20 °C ~ 50 °C
Bluetooth	BT 5.1	Humidity	95% Non-Condensing
GNSS	GPS/AGPS, GLONASS, BeiDou, Galileo, Internal antenna	Drop Height	Multiple 1.8 m drops (at least 20 times) Multiple 2.4 m drops (at least 20 times)
Vo-LTE	Support Vo-LTE HD video voice call	Rugged Feature	IP65



KRELL Informatica S.r.l. – Via Appia Nuova Km 19,200 – 00047 Marino (RM)

Tel 06 93 00 547 - 06 93 52 489 E-mail: info@krell.it – Sito: www.krell.it